



## NAC3M-TRUE1-S

The powerCON TRUE1 is a locking true mains connector for harsh and demanding applications. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 is a connector series with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.





## Features and Benefits

- Heavy duty sealed power connector for harsh and demanding environment
- Lockable single phase connector
- ENEC and VDE certified according to IEC 60320-1 and EN IEC 60320-1
- IP65 and IP67 (mated or with closed cap)
- Easy and reliable twist lock system
- Uses high impact UV-resistant materials
- Extremely robust and reliable
- UL and CSA Certified According to UL 60320-1 and CSA 22.2 No. 60320-1
- True mains connector with breaking capacity (CBC)
- Unique NEUTRIK locking bushing and strain relief for cable diameters 6 mm to 12 mm (0.23 – 0.47 inches)

## Product related questions and answers

| Question   | Answer   |
|--|--|
| What is the different between the -S and -L Version? | <p>Both versions are fully certified according to EN IEC 60320-1, UL 60320-1 and CSA 22.2 No. 60320-1.</p> <p>The S-version is certified other Cables then the L-version, cables as follows:</p> <p>S-Version: H05VV-F 3G1.5mm<sup>2</sup>, H05VV-F 3G2.5mm<sup>2</sup>, H07RN-F 3G 1.5 mm<sup>2</sup> and SJOOW 14/3 AWG.</p> <p>L-Version: H07RN-F 3G 2.5 mm<sup>2</sup>, SOOW 16/3, SJOOW 16/3 and SJOOW 14/3</p> |
| When is the IEC 60799 relevant?                      | <p>This standard applies for "Cord Sets And Interconnection Cord Sets" and therefore covers cables to the mains and cables acting as power interconnections.</p>   |
| Why is the bushing loose in one direction?           | <p>This is to meet the standards requirement to prevent disassembling by hand. In order to open the cable entry a special tool will be required.</p>   |

## Technical Information

| Product        |                 |
|----------------|-----------------|
| Title          | NAC3M-TRUE1-S   |
| Product family | powerCON® TRUE1 |

| Electrical                    |   |
|-------------------------------|---|
| Contact resistance            | ≤ 2 mΩ  |
| Dielectric strength           | 4 kVdc / 2.8 kVac   |
| Insulation resistance         | > 1 GΩ (after damp and heat test IEC 68-2-30)   |
| Number of electrical contacts | 2 + PE  |
| Rating Europe                 | 16 A / 250 V AC according to EN IEC 60320-1   |
| Rating America                | 20 A / 250 V AC according to UL 60320-1<br>20 A / 250 V AC according to CSA C22.2 No. 60320-1 |

| Mechanical                  |                                |
|-----------------------------|--------------------------------|
| Cable O.D.                  | 6 - 12 mm (0.23 – 0.47 inches) |
| Lifetime                    | > 5000 mating cycles           |
| Wiresize (mm <sup>2</sup> ) | 1.5 - 2.5 mm <sup>2</sup>      |
| Wiresize (AWG)              | 14 AWG                         |

| Material        |                   |
|-----------------|-------------------|
| Contact plating | 2 µm Ag           |
| Locking element | Polyamide (PA 66) |
| Contacts        | Copper Alloy      |
| Insert          | Polyamide (PA 66) |
| Shell           | Polyamide (PA 66) |
| Strain relief   | Polyketon         |

| Environmental               |  |
|-----------------------------|--|
| Flammability                | UL 94 V-0                                |
| Protection class            | IP 65 / 67 (mated or with closed caps)   |
| UV resistance               | F1 rated material withstands UV exposure |
| Operating temperature range | -5°C to +40°C according to IEC 60320-1   |